

Lift Table

LOADWARRIOR® SERIES

LIFT PRODUCTS SPECIFICATIONS

2,000 - 10,000 LBS. CAPACITIES



Design Highlights

- Hand-held NEMA 4X Push Button with 10' Straight Cord
- Maintenance Strut
- Self Lubricating Bushings
- Wire Braided Hydraulic Hoses
- Solid Steel Legs with Hard Chromed Pins
- Pre-wired Power Unit with UL Approved Control Panel
- Velocity Fuses on All Cylinders to Prevent Uncontrolled Descent
- Polyethylene Reservoir Allows Easy Visual Check of Oil Level or Steel Reservoir with Dip Stick
- 1 HP Single Phase with 115 VAC Control Valve
- Meets or Exceeds the ANSI MH29.1 Standard for Industrial Scissors Lifts

Available Options

- Oversized Platforms with Straight Sides
- Oversized Platform with Beveled Toe Guards. (Add 8" to Length and Width. Lowered Height Increases to 8 1/2")
- Accordion Skirting (Platform Must Be 6" Longer and Wider than Standard)
- Remote Air Operated Power Unit. Requires 70psi and 95cfm Clean Plant Air; Includes Hand Valve
- NEMA 4 Washdown Power Unit and Controls
- Increased HP Available
- 1 HP 3 Phase
- NEMA 12, Wall Mount Up/down Push Button Station
- Upper Travel Limit Switch
- High Cycle Package
- Wall Mount Push Button Station
- Foot Switch with Cover - NEMA 1
- Portability
- Other _____

Project Information

Job Name _____

Address _____

General Contractor _____

Distributor _____

Model _____ Quantity _____ Voltage/Phase _____



1612 Hutton Drive, Suite 140 • Carrollton, TX 75006, USA • Tel: 800-933-4834 • Fax: 972-389-4769 • Email: sales@sercocompany.com • www.sercocompany.com

A continuing research program is in effect at Serco. We reserve the right to incorporate product improvement at any time without prior notice.

© 2006 4Front Engineered Solutions, Inc.

Form#: SSS1037-06

Lift Table

LOADWARRIOR® SERIES

LIFT PRODUCTS SPECIFICATIONS

2,000 - 10,000 LBS. CAPACITIES

Model No.	Travel [in]	Capacity [lb]	Standard Platform & Base Frame [in]	Maximum Platform Size [in]	Lowered Height [in]	Raised Height [in]	Raise Lower Time (sec)	Ship Weight [lb]
SLT24-2	24	2,000	24 x 36	48 x 58	7	31	18	455
SLT24-4		4,000	24 x 36	48 x 58	8	32	25	640
SLT24-6		6,000	30 x 36	48 x 58	8	32	54	780
SLT24-8		8,000	36 x 36	48 x 58	10	34	62	890
SLT36-2	36	2,000	24 x 48	48 x 72	7	43	24	619
SLT36-4		4,000	24 x 48	48 x 72	9	45	48	710
SLT36-6		6,000	30 x 48	48 x 72	9	45	72	970
SLT36-8		8,000	36 x 48	48 x 72	12	48	81	1,340
SLT48-2	48	2,000	24 x 72	48 x 96	8	56	35	960
SLT48-4		4,000	24 x 72	48 x 96	9	57	70	1,000
SLT48-6		6,000	30 x 72	48 x 96	9	57	105	1,430
SLT48-8		8,000	36 x 72	48 x 96	12	60	138	1,984
SLT48-10		10,000	36 x 72	48 x 96	12	60	154	2,144
SLT59-2	59	2,000	24 x 88	48 x 102	8	67	40	1,207
SLT59-4		4,000	24 x 88	48 x 102	9	68	80	1,470
SLT59-6		6,000	30 x 88	48 x 102	9	68	120	1,850
SLT59-8		8,000	36 x 88	48 x 102	12	71	159	2,540
SLT59-10		10,000	36 x 88	48 x 102	12	71	201	2,740

